

Water Suction and Discharge Hoses — *continued*
**Heavy-Duty 112 CL Hose**  
*Suction and Discharge*

Nom. I.D. (In.)	Max. W.P. (psi)	Min. Bend Radius (In.)	Vacuum Rating (In. Hg.)	Part No.
1¼	80	3.0	29.8	1¼ 112 CL
1½	70	3.0	29.8	1½ 112 CL
2	65	4.0	29.8	2 112 CL
2½	65	5.0	29.8	2½ 112 CL
3	55	8.0	29.8	3 112 CL
4	50	10.0	29.8	4 112 CL



**Recommended for:** Economical heavy-duty water suction hose.

**Temperature range:** -13°F to +158°F (-24°C to +70°C).

**Construction:** Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.

**Color:** Clear or Solid Green.

**Extra Heavy-Duty Kanaline SR Hose**  
*Suction and Discharge*

Nom. I.D. (In.)	Max. W.P. (psi)	Min. Bend Radius (In.)	Vacuum Rating (In. Hg.)	Part No.
1½	125	2.0	28.0	1½ KL
2	125	3.5	28.0	2 KL
3	125	3.5	28.0	3 KL
4	100	7.1	28.0	4 KL
6	50	10.2	28.0	6 KL
8	50	15.7	28.0	8 KL
10	36	24.8	28.0	10 KL



**Recommended for:** Heavy-duty suction and discharge hose for use in fish suction and rental/construction pumping.

**Construction:** Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

**Temperature range:** -13°F to +158°F (-24°C to +70°C).

**Features**

- Lightweight and flexible.
- External helix provides for easy drag.
- Rated for both suction and discharge.
- Clear sidewall permits visual check of material flow.

**300 EPDM Septic, Agricultural and Marine Hose**  
*Suction and Discharge*

Nom. I.D. (In.)	Max. W.P. (psi)	Min. Bend Radius (In.)	Vacuum Rating (In. Hg.)	Part No.
1	50	1.9	29.8	1 300 EPDM
1¼	50	3.2	29.8	1¼ 300 EPDM
1½	50	3.2	29.8	1½ 300 EPDM
2	50	5.2	29.8	2 300 EPDM
2½	50	5.6	29.8	2½ 300 EPDM
3	43	7.1	29.8	3 300 EPDM
4	38	11.0	29.8	4 300 EPDM
6	23	20.0	28.0	6 300 EPDM



**Recommended for:** Heavy-duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications and marine use.

**Temperature range:** -40°F to +158°F (-40°C to +70°C).

**Construction:** EPDM rubber, polyethylene helix, smooth bore, corrugated O.D.

**Features**

- Lightweight and flexible.
- External helix provides for easy drag.
- Resistant to agricultural chemicals.